



Series 9000-MTR, Series
9000-W-MTR, 9000-W-TMTR
Components

**TECHNICAL
INFORMATION**

PROJECT: _____
LOCATION: _____
ARCHITECT: _____
ENGINEER: _____
SALES ENGINEER: _____
DATE: _____

www.monoxivent.com

info@monoxivent.com

309-794-1000

Page: HRMO-6

**MOTOR OPERATED
HOSE REEL**

SERIES: 9000-MTR, 9000-W-MTR, 9000-W-TMTR

COMPONENT LISTING

- A - Heavy Gauge Steel Support Mounting Frame
- B - End Flange
- C - Drum Assembly - 18" Diameter
- D - Duct Connection Fitting and Bearing Assembly
- E - Internal Hose Tube - 6" or 8" Diameter
- F - Hose Tracking Bar
- G - Hose to Drum Connector - 4", 5", 6", 8" Diameters
- H - Direct Drive Motor Assembly or Tube Motor
- I - Extraction Hose - 4", 5", 6", 8" Diameters

(Standard Hose Lengths are 16', 20', & 24' Other Lengths are Available - Please Contact Factory)

NOTE: Drum hose capacity for Series: 9000-MTR, 9000-W-MTR, 9000-W-TMTR

<u>Model</u>	<u>Hose Dia.</u>	<u>Max. Hose Capacity on Drum</u>	<u>Drum Diameter</u>	<u>Drum Width</u>
9000-MTR	4"	25'	18"	19"
9000-MTR	5"	20'	18"	19"
9000-MTR	6"	20'	18"	19"
9000-W-MTR	4"	40'	18"	28"
9000-W-MTR	5"	34'	18"	28"
9000-W-MTR	6"	32'	18"	28"
9000-W-TMTR	4"	40'	18"	28"
9000-W-TMTR	5"	34'	18"	28"
9000-W-TMTR	6"	32'	18"	28"
9000-W-TMTR	4"	50'	18"	32"
9000-W-TMTR	5"	40'	18"	32"
9000-W-TMTR	6"	36'	18"	32"
9000-W-TMTR	8"	24'	18"	32"

Drum capacity is listed for information only. This does not reflect the length of hose supplied on the hose reel.

NOTE: The above hose lengths are for industry standard. Hose reels can be supplied with longer lengths of hose. Please consult the factory.