



Portable Vertical Stack Cane  
Fan Models - Component  
Listing

**TECHNICAL  
INFORMATION**

PROJECT: \_\_\_\_\_  
 LOCATION: \_\_\_\_\_  
 ARCHITECT: \_\_\_\_\_  
 ENGINEER: \_\_\_\_\_  
 SALES ENGINEER: \_\_\_\_\_  
 DATE: \_\_\_\_\_

www.monoxivent.com

info@monoxivent.com

309-794-1000

Page: PVSC-6



**Portable Vertical Stack Cane - ELIMINATOR**

**Component List - Fan Models**

- A - Discharge Hose Storage Mast
- B - 25' x 6" High Compression Discharge Hose (Series 7300)
- C - Push Handle
- D - Fan On/Off Heavy Duty Switch
- E - 45' Power Cord with Plug. Note, power cord stored on a lock and latch spring retractor assembly
- F - TEFC 1.5 HP, 1 Phase, 3450 RPM Blower. Aluminum Wheel and Housing.
- G - Foot Brake
- H - 5" Solid Hard Rubber Wheels. Two Fixed and Two Swivel.
- I - Vertical Stack Nozzle, with 8" Mouth Opening.
- J - Upper Telescoping Nozzle Mast - 1 7/8" Galvanized Tube.
- K - Female Quick Release Coupler, for Mast Hose.
- L - Male Quick Release Coupler, for Mast Hose
- M - Upper Mast Height Adjustment, Locking Mechanism
- N - Lower Telescoping Nozzle Mast, 2" Galvanized Tube
- O - 6" High Compression Inlet Hose, 600-Degree, Series 7600.
- P - 180-Degree Blower, Swivel Fitting - Allows the Fan Discharge to Rotate in the Direction that the Discharge Hose Must Exit
- R - Nozzle Storage Mast (For Storage of the Optional 8006-VG Under Chassis Nozzle)
- S - 3/16" Steel Base Plate Assembly. Laser Cut and Machine Bent. Powder Coat Finish.

**Blower Performance:**

Model	HP	1"	2"	3"	4"	5"	6"	7"
D15	1.5	965	910	840	780	675	550	330

\* This blower is constructed of aluminum (housing and wheel). The wheel is of a radial type. The motor is a TEFC Baldor - UL and CSA rated. Motor: 3450 RPM.