



Portable Exhauster  
Series PFE  
Component Listing

**TECHNICAL  
INFORMATION**

PROJECT: \_\_\_\_\_  
LOCATION: \_\_\_\_\_  
ARCHITECT: \_\_\_\_\_  
ENGINEER: \_\_\_\_\_  
SALES ENGINEER: \_\_\_\_\_  
DATE: \_\_\_\_\_

[www.monoxivent.com](http://www.monoxivent.com)

[info@monoxivent.com](mailto:info@monoxivent.com)

309-794-1000

Page: WSC-30

**PORTABLE FUME EXHAUSTER**  
**COMPONENT LISTING**

- A. Internal self support flex arm (7', 10', or 14') 6" hose
- B. 360-Degree swivel mounting elbow
- C. Hood with handle
- D. Steel pipe with 5/64 wall thickness - 6" diameter
- E. Push handle with power cord holder
- F. Direct drive pressure blower - Baldor TEFC Motor - UL & CSA
- G. Portable base plate - 30" x 30" x 1/2" - solid steel plate
- H. Swivel casters with foot lock
- J. Clean out access cover

**\*\* Notes:**      *The PFE is supplied standard with a 1.5 HP motor.  
The wheel and housing are constructed of aluminum.  
Higher horse power fans available upon request.*